



## OBMW2.E101843 Magnet Wire - Component

[Page Bottom](#)

### Magnet Wire - Component

[See General Information for Magnet Wire - Component](#)

**DAHRENTRAD AB**

E101843

JONSLUND

SE-465 80 NOSSEBRO, SWEDEN

Mtl Dsg	Mark Dsg	Coat Typ			ANSI Type	Temp Class
		BC	OC			
<b>Magnet wire</b>						
Datherm	—	Polyester-imide	—	MW-30	180	
Damid	—	Polyester-imide	Polyamide-imide	MW-35#	200	
Damid PE	—	Polyester	Polyamide-imide	MW37	220	
				MW35#	200	
Damid2	—	Polyester-imide	Polyamide-imide	MW37	220	
				MW35#	200	
Damid CR	—	Theic-Modified Polyesterimide	Polyamideimide	MW37	220	
DASOL 180	—	Polyurethane	—	MW 82	180	
Mtl Dsg	Mark Dsg	Coat Type			ANSI Type	Temp Class
		BC	OC	BOND		
<b>Bondable Magnet wire</b>						
Damidbond	—	Polyester-imide	Polyamide/imide	Aromatic Polyamide*	@ MW102	200 180#

(\*) Self-bonding top coat.

@ Non-ANSI Type

# The magnet wire may perform better than the rating reflects and may not be suitable for insulation system, varnish or end product testing. Further consideration is necessary prior to its use in testing

Marking: Company name and material designation or marked designation on package or reel.

[Last Updated](#) on 2012-09-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".